



上海条码



关闭

关于公司

条码产品

自主开发

应用方案

下载中心

条码知识

人才招聘

在线解答



▶ www.tiaoma.org.cn

条码产品

当前位置: 条码打印机 > Zebra条码打印机 > Zebra TTP 8200条码打印机

条码打印机

- 美国Intermec条码打印机
- 日本Tec条码打印机
- 美国Zebra条码打印机
- 日本Sato条码打印机
- 日本Ring条码打印机
- 美国Datamax条码打印机
- 日本Citizen条码打印机
- 日本Shinsei条码打印机
- 日本Toshiba条码打印机
- 美国Printronix条码打印机
- 台湾Godex条码打印机
- 台湾TSC条码打印机
- 韩国Woosim条码打印机
- 德国CAB条码打印机

条码扫描器

数据采集器

条码软件


条码检测仪

条码标签

条码碳带

条码打印机配件

无线条码产品



Zebra TTP 8200 Thermal Receipt Printers

The TTP 8200 series kiosk printers offer 203-dpi resolution for full-format A4 or letter-size printouts of forms, bank statements, maps, or Web pages. The fast, compact, and low-maintenance design makes these printers ideal for unattended environments. The pull detector and jam-preventing loop presenter provide trouble free operation. The retract function keeps sensitive documents from being left behind outside the kiosk - and it saves media. If a printout is not taken from the printer, the output will be retracted and the remaining information can be deleted from the print queue, eliminating unwanted print jobs. The TTP 8200 is available in three configurations for flexible kiosk integration: standard, compact, and vertical, each equipped with standard USB and parallel interfaces. For additional configuration flexibility, the media can be mounted either behind or below the printer.

Standard Features

- USB and IEEE-1284 interfaces
- Printer Specifications
- Resolution 203 dpi (8 dots/mm)
- Print width 8.5" (216 mm)
- Print length Letter: 11" (279 mm) A4: 11.7" (297 mm)

Print speed 3.94" (100 mm)/sec

Media Characteristics

- Maximum roll diameter 9.84 (250 mm)
- Core diameter 1" (25 mm)
- Media thickness .002" (.054 mm) to .004" (.1 mm)
- Media types continuous, fanfold

Operating Characteristics

- Operating temperature DT: Operating temperature 32° F (0° C) to 122° F (50° C) Direct thermal
- Storage temperatures 4° F (-20° C) to 140° F (60° C)
- Operating humidity 35-75% non-condensing R.H.
- Storage humidity 10-90% non-condensing R.H.
- Electrical 24 VDC, ± 10%, average 6 A, peak 12 A
- Agency approvals UL cUL CE

Physical Characteristics

- Width 11.3" (286 mm)
- Height 3.07" (78 mm)
- Depth 6.73" (171 mm)
- Weight 10.58 lbs (4.8 kg)

Related Products

Options

- Paper near end sensor
- weekend paper low sensor
- RS-232 Serial interface
- Communication and Interface Capabilities
- Parallel IEEE-1284 and USB
- Optional external RS-232 Serial
- Windows and Linux drivers. Direct addressing with ESC sequences.

Bar Codes/Symbologies

Linear


销售热线

- 上海条码:021-51088451
- 广州条码:020-11381938
- 珠海条码:0756-2157363
- 深圳条码:0755-31866102
- 中山条码:0760-4194055
- 东莞条码:0755-51866036
- 北京条码:010-61126024
- 济南条码:0531-71754213
- 四川条码:待建中
- 沈阳条码:待建中
- 佛山条码:待建中
- 西安条码:待建中
- 长春条码:待建中
- 哈尔滨条码:待建中
- 武汉条码:待建中
- 厦门条码:待建中
- 兰州条码:待建中

热销推荐

- CASIO dt-940数据采集器
- symbol MC3090数据采集器
- symbol LS1203条码扫描器
- symbol LS9208条码扫描器
- symbol LS4208工业条码扫描器
- symbol LS3478无线条码扫描器
- symbol LS3008工业条码扫描器
- zebra 105s1工业条码打印机
- zebra 888TT商业桌面条码打印机

Code 39  
Fonts and Graphics  
Up to eight bitmap fonts

版权所有 © 上海条码网 

电话: 021-51088451 51088452 传真: 021-50935062

地址: 上海市浦东大道1097弄15号楼4E室 邮编: 200135 邮箱: mail#tiaoma.org.cn