

▶ 条码网首页 ▶ 条码网地图 ▶ 条码新闻 ▶ 联系我们



上海条码

关于公司

条码产品

自主开发

应用方案

下载中心

条码知识

人才招聘

在线解答



条码打印机  
条码扫描器

美国intermec条码扫描器  
美国Symbol条码扫描器  
意大利Datalogic条码扫描器  
HHP(honeywell)条码扫描器  
日本Opticon条码扫描器  
美国Metrologic条码扫描器  
美国Psc条码扫描器  
美国Microscan条码扫描器  
福建新大陆条码扫描器  
台湾CipherLAB条码扫描器  
日本DENSO条码扫描器  
台湾young条码扫描器

数据采集器

条码软件

条码检测仪

条码标签

条码碳带

条码打印机配件

无线条码产品

当前位置: 条码扫描器 > Symbol条码扫描器 > Symbol LS3008条码扫描器

## Symbol LS3008条码扫描器



最大扫描速度:  
200线/秒  
分辨率:  
5mil  
最大扫描距离:  
48.25 cm  
光源类型:  
650, 可视激光二极管

LS3008 坚固耐用的手持式扫描器采用轻便的人体工程学设计, 以经济价位提供出色性能和耐用性, 可为轻工业、医疗和零售行业带来更高生产力。

LS3008 的单板结构旨在确保最高可靠性和最长的稳定运行时间, 可消除扫描器采用多个电路板和连接带式电缆时最常见的故障点。

其他优势:

创新的多线光栅扫描模式使操作人员扫描时无需精确对准扫描物品和调整扫描器的位置; 可轻松扫描较小、堆叠、印刷质量较差的条码

液态聚合物扫描技术消除了摩擦和磨损, 从而确保了出色的耐用性和可靠性

出色的移动容错功能可以减少用户的疲劳感, 使用户可以快速连续地扫描条码, 而感觉不到延迟, 从而提高生产力

适用于扫描从 0 到 19 英寸的各种物品, 提供舒适、直观的扫描

远程扫描器管理 (RSM) 可大大减轻管理负担并降低管理成本

可选的 Intellistand 可方便地在免提模式和手持模式之间进行切换, 从而使操作人员保持最高生产力

The LS3008 rugged handheld scanner delivers affordable performance and durability in a lightweight ergonomic design for superior productivity in light industrial, healthcare and retail environments.

Designed to deliver maximum reliability and uptime, the LS3008's single board construction eliminates multiple circuit boards and connecting ribbon cables the most common point of failure in scanners.

Additional benefits:

Innovative multi-line rastering scan pattern eliminates the need for exact aim and positioning, and captures even tiny, stacked and poorly printed bar codes

Liquid Polymer Scan Technology eliminates friction and wear, providing superior durability and reliability

Superior motion tolerance reduces fatigue and increases productivity by enabling users to scan bar codes in rapid succession without delay

Wide working range from 0 to 19 inches provides comfortable, intuitive scanning

Remote Scanner Management (RSM) support dramatically reduces management effort and cost

Optional Intellistand provides the versatility to switch between hands-free and handheld modes to obtain maximum productivity

Features Benefits

Single board construction Eliminates the most common point of failure ribbon cables between multiple circuit boards

Drop specification: 6.5 ft./2m drops to concrete at room temperature Maximizes reliability and uptime

IP53 sealing Can be safely wiped down and sanitized for clean manufacturing and hospital environments

Liquid Polymer Scan element with lifetime warranty Eliminates friction and wear for superior durability and reliability

Wide working range from 0 to 19 inches Enables comfortable, intuitive scanning

销售热线

- 上海条码:021-51088451
- 广州条码:020-11381938
- 珠海条码:0756-2157363
- 深圳条码:0755-31866102
- 中山条码:0760-4194055
- 东莞条码:0755-51866036
- 北京条码:010-61126024
- 济南条码:0531-71754213
- 四川条码:待建中
- 沈阳条码:待建中
- 佛山条码:待建中
- 西安条码:待建中
- 长春条码:待建中
- 哈尔滨条码:待建中
- 武汉条码:待建中
- 厦门条码:待建中
- 兰州条码:待建中

热销推荐

- CASIO dt-940数据采集器
- symbol MC3090数据采集器
- symbol LS1203条码扫描器
- symbol LS9208条码扫描器
- symbol LS4208工业条码扫描器
- symbol LS3478无线条码扫描器
- symbol LS3008工业条码扫描器
- zebra 105sl工业条码打印机
- zebra 888TT商业桌面条码打印机

Ability to read down to 3 mil bar codes Enables effortless scanning of smaller bar codes

Scratch resistant tempered glass exit window Delivers continuously reliable scanning

Superior motion tolerance Enables scanning of bar codes in rapid succession without delay; reduces fatigue and increases productivity

Multi-line rastering scan pattern Delivers superior scanning performance; eliminates need for exact aim and positioning; captures even tiny, stacked and poorly printed bar codes

Multiple onboard interfaces including RS232, USB and KBW (keyboard wedge)

Simplifies installation and integration; ensures compatibility with host/POS today and tomorrow

Remote Scanner Management (RSM) support Discover, provision and upgrade devices from a central remote location; dramatically reduces management effort and costs

Optional Intellistand for hands-free mode Ability to switch between hands-free and handheld modes for maximum productivity and comfort

#### LS3008 Specification Highlights

##### Physical Characteristics:

Dimensions: 6.7 in. H x 3.7 in. L x 2.7 in. W

17 cm H x 9.3 cm L x 6.8 cm W

Weight: Approximately 6.4 oz./181 gm

Voltage and Current: 5 +/- 10%VDC @ 140 mA (Stand by: <35 mA)

Color: Yellow/Twilight Black

##### Performance Characteristics:

Light Source: 650 nm laser diode

Motor Frequency: 50Hz

Decode Rate: 200 decodes per second

Roll/Pitch/Yaw: +/- 35; +/- 60; +/- 60

Nominal Working Distance: 13 mil (100% UPC/EAN): 0 to 19 in. (48.25 cm)

5 mil (Code 39): 1.25 to 5.25 in. (3.17 to 13.33 cm)

Print Contrast: 25% minimum reflectance

Motion Tolerances: Horizontal velocity: 200 in. (508 cm)/second

Vertical velocity: 200 in. (508 cm)/second

Angular velocity: 200 in. (508 cm)/second

Decode Capability: UPC/EAN and with supplementals, Code 39, Code 39 Full ASCII,

Tri-optic Code 39, RSS Variants, UCC/EAN 128, Code 128, Code 128 Full ASCII, Code

93, Codabar (NW1), Interleaved 2 of 5, Discrete 2 of 5 MSI, Codell, IATA, Bookland

EAN, Code 32

Interfaces Supported: RS-232C (Standard, Nixdorf, ICL, & Fujitsu); IBM 468x/469x;

Keyboard Wedge; USB (Standard, IBM SurePOS, Macintosh); Laser/Wand Emulation; In

addition Synapse Adaptive Connectivity allows for connectivity to all of the above

plus many non-standard interfaces

##### User Environment:

Operating Temperature: 32 to 122 F/0 to 50 C

Storage Temperature: -40 to 158 F/-40 to 70 C

Humidity: 5% to 95% non-condensing

Drop Specification: Withstands multiple 6.5 ft./2 m drops to concrete at room temperature; 6 ft./1.825 m drops to concrete at all other operating temperatures

Environmental Sealing: Sealed at IP53 against dust and water

Ambient Light Immunity: Immune to normal artificial indoor and natural outdoor

(direct sunlight) lighting conditions

##### Regulatory

Electrical Safety: Certified to UL1950, CSA C22.2 No. 950, EN60950/IEC950

EMI/RFI: FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive,

Australian SMA

Laser Safety: CDRH Class II, IEC Class 2

##### Accessories

Mounting Options: Intellistand with adjustable height: 5 to 10 in./12.7 to 25.4 cm

and adjustable angle between 0 to 90; desktop and wallmount holders; scanner sleeve

with integrated loop for tether attachment

Power Supplies: Power supplies are available for applications that dont supply

power over the host cable

版权所有 © 上海条码网 

电话: 021-51088451 51088452 传真: 021-50935062

地址: 上海市浦东大道1097弄15号楼4E室 邮编: 200135 邮箱: mail#tiaoma.org.cn